

P Series 4K NVR

ONR-P3-7116



System

Compression	Standard H.265
OS	Embedded Linux

Video

Network Input	16 CH IP Camera input
Network Access Bandwidth	80Mbps
Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps
Output	HDMI x 1 : 4K x 2K / 1920 x 1080 / 1280 x 1024; HDMI-VGA cable optional, 1920 x 1080 / 1280 x 1024

Audio

Network Input	16 CH IP Camera audio input
2-way Audio	RCA x 1
Local Output	RCA x 1

Record

Record Stream	Dual stream recording
Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
Mode	Manual, timer, motion, sensor

Playback

Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

Alarm

Mode	Manual, sensor, motion, exception
Input	4 CH local input, 16 CH IP Camera alarm input
Output	1 CH
Triggering	Record, snap, preset, e-mail, etc.

Network

Interface	RJ45 10 / 100 Mbps x 1
PoE Port	No
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Max 10 users online

Mobile Device

OS	iOS, Andriod
----	--------------

Storage

HDD	SATA x 1
-----	----------

Backup

Local Backup	U disk, USB mobile HDD
Network Backup	Yes

Port

USB	USB 2.0 x 2 (one in the front panel and the other in the rear panel)
Remote Controller	Optional

Others

Power Supply	DC12V
Consumption	<= 5W (without HDD)
Dimensions(mm)	380 x 248 x 52 (W x D x H)
Work Environment	- 10 °C ~ 50 °C, 10 % ~ 90 % humidity

Up to 8MP NVR



Summary

ONR-P3-7116 series are 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system. ONR-P3-7116 support 16 CH IP input, simultaneous 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial,commerce, enterprise, transportation and government, etc.

Features

- * Support 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- * Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- * Intuitive and user-friendly Graphic User Interface (GUI), Windows styleoperation by mouse
- * Multi-mode recording: manual / timer / motion / sensor
- * Playback : 16 CH simultaneous playback
- * Search : time slice, time, event (manual,sensor, motion), tag search
- * Express and flexible backup via USB, network and so on
- * Pentaplex : preview, record, playback, backup and remote access
- * DHCP, DDNS, PPPoE network protocol and CMS supported
- * Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- * Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- * Multi-user online simultaneously
- * Authorization management, log view and device status view
- * 4K output, true high resolution display
- * Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- * Support NAT function and QRCode scanning by mobile phone and PAD
- * Powerful smart phone & Pad surveillance with iOS and Andriod OS

